

HERITAGE MEDCALL TECHNICAL SPECIFICATIONS

Model HM-1210W Universal Door / Window Transmitter

- 900 Mhz Spread Spectrum
- Uses Standard Door Contacts
- Non-volatile memory retains programming data



DESCRIPTION:

The HM-1210W Universal Door / Window Transmitter provides a fully supervised reduced size transmitter for monitoring door and window contacts. Includes one internal magnetic reed switch. The magnet will allow a 5/8" gap. No external wiring required. Tamper resistive case with tamper indication. Available in off-white.

MOUNTING:

Snap-in mounting bracket included for quick installation and removal.

DIMENSIONS:

3.5"W X 1.7"L X 0.9" D

POWER:

Includes 3.0V Lithium battery.
Average Battery Life 4 – 5 years.
Battery type: DL123A

Specifications:

External contacts: N/O or N/C
Operating environment: 32 to 140°F (0 to 60°C)

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The universal transmitter shall be a HM-1210W supplied by Heritage MedCall. The universal transmitter shall be capable of communicating with the Sentry Freedom wireless repeater(s) and receiver. The universal transmitter shall supervise operation and report any troubles along with low battery warning to the Sentry Freedom software. The universal transmitter shall be capable of monitoring a normally open or normally closed door/window contact. The universal transmitter will not require any external wiring. The universal transmitter shall include a snap-in mounting bracket for installation and a 3V lithium battery.