

TECHNICAL SPECIFICATIONS

MULTI-SECTIONAL DOME LAMP

HM-DM1, HM-DM2, HM-DM3, HM-DM4

MAXIMUM VISIBILITY

FOUR LAMP COLORS
AVAILABLE

PLUG IN BULBS

FLEXIBLE INSTALLATION



Front

Rear

DESCRIPTION

The multi-sectional dome lamp, DM-1 thru DM-4, shall be surface, wall or ceiling mounted available for use as 1 section (single) to 4 section dome lamp.

LAMP

Bayonet type, long life incandescent lamps rated at 100 mA at 28 volts DC each, replaceable from the front. Available colors; white, red, green or amber.

INSTALLATION

Prewired connectors to facilitate easy installation. Mount using only the four 6-32 x 1" nylon screws provided.

HOUSING AND FINISH

Faceplate: High impact molded ABS with flame retardant properties finished in off-white.

Dome Lens: High impact translucent acrylic with flame retardant properties finished in white translucent.

DIMENSIONS

Faceplate & Dome Lens: 4 ½" (11.43cm) high x 4 9/16" (11.59cm) wide x 3" (7.62cm) deep.

W42 Backbox: 4-11/16" (11.91cm) wide square electrical backbox with two gang adapter for total depth of 2-7/8" (7.30cm), supplied by others.

LISTINGS

The HM-DM# is UL listed Hospital Signaling Equipment / Nurse Call Equipment under file number E206037.

Heritage Medcall, Inc.

202 East Virginia Avenue, Tampa, FL 33603
813-221-1000 (voice), 813-223-1405 (fax)
www.heritagemedcall.com

01/04 HM-DM-# Issue C

Printed in U.S.A.

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

MODEL HM-DM-# MULTI-SECTIONAL DOME LAMP

The multi-sectional dome lamp, DM-1 thru DM-4, shall be surface, wall or ceiling mounted available for use as 1 section (single) to 4 section dome lamp.

The HM-DM-# shall be UL and CUL listed Hospital Signaling Equipment / Nurse Call Equipment under file number E206037.

The lamps shall be Bayonet type, long life incandescent lamps rated at 100 mA at 28 volts DC each, replaceable from the front. Available colors; white, red, green or amber.

The HM-DM# shall use prewired connectors to facilitate easy installation and mount using only the four 6-32 x 1" nylon screws provided.

The faceplate shall be of high impact molded ABS with flame retardant properties finished in off-white. The dome lens shall be of high impact translucent acrylic with flame retardant properties finished in white translucent.

The Faceplate & Dome Lens shall be 4 ½" (11.43cm) high x 4 9/16" (11.59cm) wide x 3" (7.62cm) deep. **W42 Backbox:** 4-11/16" (11.91cm) wide square electrical backbox with two gang adapter for total depth of 2-7/8" (7.30cm), supplied by others.