


TECHNICAL SPECIFICATIONS

FORTY LAMP ANNUNCIATOR PANEL

HM-A40

Displays System Status
Low-Power High-Visibility Lamps
Variety of Lens Colors Available
Connections via Prewired Connectors



Front

Rear

DESCRIPTION

Wall recessed or surface mounted forty lamp call annunciator panel providing visual system status indication via forty lamp positions.

INDICATORS

Forty low-power high visibility lamps. Standard lens color is white, others available separately include: red, amber, green, blue, yellow and clear.
Custom laminated labels are available for lenses.
Lamps are rated 24 VDC at 40 mA.
Lamps are front replaceable with rated average life of 6000 hours.

LISTINGS

The HM-A40 is UL and CUL listed Hospital Signaling Equipment / Nurse Call Equipment under File E157381.

INSTALLATION

Plugs into prewired connectors.
HM-A40 requires four HM-11P
Mounts onto backbox with four 6-32 x 1" nylon screws provided.

HOUSING AND FINISH

Faceplate: punched aluminum faceplate with baked epoxy finish, finished in off white.

DIMENSIONS

Faceplate: 8-1/2" (21.59cm) wide x 11" (27.94cm) high.

W2 Backbox: 7-1/2" (19.05cm) wide x 10" (25.4cm) high x 3 1/2" (8.89 cm) deep, available separately from Heritage.

Heritage Medcall, Inc.

202 East Virginia Avenue, Tampa, FL 33603
813-221-1000 (voice), 813-223-1405 (fax)
www.heritagemedcall.com

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

MODEL HM-A40 FORTY POSITION ANNUNCIATOR PANEL

The wall recessed or surface mounted HM-A40 Forty Position Annunciator Panel shall provide visual status indication via 40 lamp positions.

The panel shall provide forty low-power high-visibility indicator lamps. Lamps shall be front panel replaceable with an average rated life of 6000 hours. Standard lens color shall be white. Others lens colors available separately shall be red, amber, green, blue, yellow, and clear.

The HM-A40 is UL and CUL listed Hospital Signaling Equipment / Nurse Call Equipment under File E157381.

The faceplate shall be metal, finished in off-white and flame retardant. For ease of installation, the annunciator panel shall plug into pre-wired connectors.

Faceplate shall mount to backbox with four 6-32 x 1" nylon screws provided.

Annunciator panel shall install into a W2 steel electrical backbox for wall flush mounting. The dimensions shall be: **Faceplate** - 8-1/2" (21.59cm) wide x 11" (27.94cm) high; **W2 backbox** - 7-1/2" (19.05cm) wide x 10" (25.40cm) high x 3 1/2" (8.89cm) deep, for total depth of 3-3/4" (9.53cm), available from Heritage.