

TECHNICAL SPECIFICATIONS

CENTRAL TONE UNIT / RING

HM-CTU/R

Provides Audible Indication
Adjustable Volume Settings
Distinctive Ring Tone
Flame Retardant Faceplate
Minimum Wiring for Easy Installation



Front



Rear

DESCRIPTION

Wall recessed or surface mounted central tone unit with distinctive ring tone to provide audible indication of system status / feature activation.

CONTROLS AND INDICATORS

Tone signals indicate feature activation via adjustable tone module.

CIRCUITRY

Solid state circuitry, front adjustable tone module for volume adjustment provides variable attenuation up to 20dB typical.

Tone: 93 db at 2 feet.

INSTALLATION

Color-coded prewired terminations provided.

Mount using only the two 6-32 x 1" nylon screws provided.

HOUSING AND FINISH

Faceplate: Flame retardant ABS plastic rated 94V-O, finished in off-white supplied with nylon mounting screws.

W41 Backbox: metal backbox supplied by others.

DIMENSIONS

Faceplate: 2-3/4" (6.99cm) wide x 4-1/2" (11.43cm) high.

W41 Backbox: 4-11/16" (11.91cm) square electrical box with one-gang adapter for a total depth of 2-7/8" (7.30cm), supplied by others.

Heritage Medcall, Inc.

202 East Virginia Avenue, Tampa, FL 33603
813-221-1000 (voice), 813-223-1405 (fax)
www.heritagemedcall.com

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

MODEL HM-CTU CENTRAL TONE UNIT / RING

The wall recessed or surface mounted tone module shall provide audible indication of system status and/or feature activation.

Tone signals shall indicate system status/feature activation via the adjustable tone module.

The unit shall be provided with an adjustable tone shutter for tone volume adjustment. To insure long life and reliability, solid state signal circuitry shall be used.

The unit shall be provided with color-coded prewired terminations for ease of installation. The faceplate shall be flame retardant ABS plastic rated 94V-O by UL, finished in off-white. Nylon screws shall be provided to mount the faceplate.

The W41 backbox shall be supplied by others. The dimensions shall be: **Faceplate:** 2-3/4" (6.99cm) wide x 4-1/2" (11.43cm) high, **W41 backbox:** 4-11/16" (11.91cm) square electrical box with one-gang adapter for total depth of 2-7/8" (7.30cm), supplied by others.